


Datasheet

Description	100% polypropylene needle punched tennis surface with total impregnation, in-filled with EPDM granulate.
Destination	Indoor tennis courts.
Support layer	Hot-rolled asphalt or concrete. Base planarity has to be checked prior to installation. Any deviations of 6 mm under the rule of 3 meters will be tolerated. Outside this limit the base has to be fixed with appropriate technical solution.
Colours	Red: 2 tones, Green: 2 tones, Blue: 2 tones, Grey
Membrane Mass	1.400 g/m ² ± 10 %
Membrane Thickness	8 mm ± 10 %
Standard roll Width	2 m
Standard roll Length	36,20 m
Standard roll Weight	approx. 101 kg
Court markings	Inlaid 50 mm wide white lines of the same textile as the playing surface.
Infill	0,5-1,5 mm EPDM granulate. Recommended quantity 300-400 g/m ² , which should be maintained throughout the life of the surface. Minimum quantity 150 g/m ²
Adhesive	Adhesive at a rate of approx 750 g/m ²
Playing features	ITF Category 3 «Medium» 
Warranty	5 years Degressive Warranty (see warranty conditions, available upon request)
Maintenance	See TOP SLIDE® Maintenance Guidelines
Installation	See TOP SLIDE® Installation Guidelines
Certification	ISO 9001:2015. Certificate Number: IT 240282

We reserve the right to amend these specifications.